



Rough Opening & Door Frame Dimensions

Interior Doors Bypass Doors (2 slabs)

1/2" DRYWALL WRAPPED OPENING			1/2" DRYWALL WRAPPED WITH HALF JAMB/CASING MILLWORK			FULL JAMB/CASING MILLWORK WRAP		
Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches	Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches	Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches
3068	n/a	36 x 83	3068	34 3/4 x 82 3/8	36 x 83	3068	36 1/2 x 83 1/4	37 x 83 1/2
3468	n/a	40 x 83	3468	38 3/4 x 82 3/8	40 x 83	3468	40 1/2 x 83 1/4	41 x 83 1/2
3868	n/a	44 x 83	3868	42 3/4 x 82 3/8	44 x 83	3868	44 1/2 x 83 1/4	45 x 83 1/2
4068	n/a	48 x 83	4068	46 3/4 x 82 3/8	48 x 83	4068	48 1/2 x 83 1/4	49 x 83 1/2
4468	n/a	52 x 83	4468	50 3/4 x 82 3/8	52 x 83	4468	52 1/2 x 83 1/4	53 x 83 1/2
4868	n/a	56 x 83	4868	54 3/4 x 82 3/8	56 x 83	4868	56 1/2 x 83 1/4	57 x 83 1/2
5068	n/a	60 x 83	5068	58 3/4 x 82 3/8	60 x 83	5068	60 1/2 x 83 1/4	61 x 83 1/2
5468	n/a	64 x 83	5468	62 3/4 x 82 3/8	64 x 83	5468	64 1/2 x 83 1/4	65 x 83 1/2
5868	n/a	68 x 83	5868	66 3/4 x 82 3/8	68 x 83	5868	68 1/2 x 83 1/4	69 x 83 1/2
6068	n/a	72 x 83	6068	70 3/4 x 82 3/8	72 x 83	6068	72 1/2 x 83 1/4	73 x 83 1/2

*RO WIDTH = DOOR CALL-OUT WIDTH

*RO HEIGHT = DOOR CALL-OUT HEIGHT + 3"

*Assumes standard 3/4" undercut

*RO WIDTH = DOOR CALL-OUT WIDTH

*RO HEIGHT = DOOR CALL-OUT HEIGHT + 3"

*Assumes standard 3/4" undercut

*RO WIDTH = DOOR CALL-OUT WIDTH + 1"

*RO HEIGHT = DOOR CALL-OUT HEIGHT + 3 1/2"

*Assumes standard 3/4" undercut

I