



## Rough Opening & Door Frame Dimensions

# Interior Doors

## Double Bifold Doors (4 slabs)

1/2" DRYWALL WRAPPED OPENING			1/2" DRYWALL WRAPPED WITH HALF JAMB/CASING MILLWORK			FULL JAMB/CASING MILLWORK WRAP		
Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches	Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches	Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches
4068	n/a	49 1/4 x 81 3/4	4068	48 5/8 x 81 1/4	49 3/4 x 81 3/4	4068	49 1/2 x 81 5/8	50 x 82 1/2
4868	n/a	57 1/4 x 81 3/4	4868	56 5/8 x 81 1/4	57 3/4 x 81 3/4	4868	57 1/2 x 81 5/8	58 x 82 1/2
5068	n/a	61 1/4 x 81 3/4	5068	60 5/8 x 81 1/4	61 3/4 x 81 3/4	5068	61 1/2 x 81 5/8	62 x 82 1/2
5468	n/a	65 1/4 x 81 3/4	5468	64 5/8 x 81 1/4	65 3/4 x 81 3/4	5468	65 1/2 x 81 5/8	66 x 82 1/2
6068	n/a	73 1/4 x 81 3/4	6068	72 5/8 x 81 1/4	73 3/4 x 81 3/4	6068	73 1/2 x 81 5/8	74 x 82 1/2
7068	n/a	85 1/4 x 81 3/4	7068	84 5/8 x 81 1/4	85 3/4 x 81 3/4	7068	85 1/2 x 81 5/8	86 x 82 1/2
8068	n/a	97 1/4 x 81 3/4	8068	96 5/8 x 81 1/4	97 3/4 x 81 3/4	8068	97 1/2 x 81 5/8	98 x 82 1/2

\*RO WIDTH = DOOR CALL-OUT WIDTH + 1 1/4"

\*RO HEIGHT = DOOR CALL-OUT HEIGHT + 1 3/4"

\*Assumes standard 3/4" undercut

\*RO WIDTH = DOOR CALL-OUT WIDTH + 1 3/4"

\*RO HEIGHT = DOOR CALL-OUT HEIGHT + 1 3/4"

\*Assumes standard 3/4" undercut

\*RO WIDTH = DOOR CALL-OUT WIDTH + 2"

\*RO HEIGHT = DOOR CALL-OUT HEIGHT + 2 1/2"

\*Assumes standard 3/4" undercut