



Rough Opening & Door Frame Dimensions

Exterior Doors

90-Minute HM with Timely Steel Frame

Single Swing Doors

Double Swing Doors

Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches	Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches	Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches
2668	31 1/2 x 81 3/4	19 1/4 x 83	5068	62 x 81 3/4	63 x 83	2868	n/a	33 1/4 x 82
2868	33 1/2 x 81 3/4	25 1/4 x 83	5468	66 x 81 3/4	67 x 83	3068	n/a	37 1/4 x 82
21068	35 1/2 x 81 3/4	29 1/4 x 83	5868	70 x 81 3/4	71 x 83			
3068	37 1/2 x 81 3/4	31 1/4 x 83	6068	74 x 81 3/4	73 x 83			
3268	39 1/2 x 81 3/4	33 1/4 x 83	7068	86 x 81 3/4	87 x 83			
3668	43 1/2 x 81 3/4	37 1/4 x 83						

*RO WIDTH = DOOR CALL-OUT WIDTH + 2 1/2"

*RO HEIGHT = DOOR CALL-OUT HEIGHT + 3"

*Assuming slabs are 79" in height w/ standard inswing threshold

*FOR OUTSWING THRESHOLD, SUBTRACT 1" FROM RO HEIGHT

*FOR ADA THRESHOLD, SUBTRACT 3/4" FROM RO HEIGHT

*RO WIDTH = DOOR CALL-OUT WIDTH + 3"

*RO HEIGHT = DOOR CALL-OUT HEIGHT + 3"

*Assuming slabs are 79" in height w/ standard inswing threshold

*FOR OUTSWING THRESHOLD, SUBTRACT 1" FROM RO HEIGHT

*FOR ADA THRESHOLD, SUBTRACT 3/4" FROM RO HEIGHT

*Slabs are 79 1/4" in height

*FOR ADA THRESHOLD, SUBTRACT 3/4" FROM RO HEIGHT

