



Rough Opening & Door Frame Dimensions

Interior Doors

Single Bifold Doors (2 slabs)

1/2" DRYWALL WRAPPED OPENING			1/2" DRYWALL WRAPPED WITH HALF JAMB/CASING MILLWORK			FULL JAMB/CASING MILLWORK WRAP		
Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches	Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches	Door Size Foot - Inch	OD Frame Size W x H in inches	Rough Opening W x H in inches
1668	n/a	19 1/4 x 81 3/4	1668	18 5/8 x 81 1/4	19 3/4 x 81 3/4	1668	19 1/2 x 81 5/8	20 x 82 1/2
2068	n/a	25 1/4 x 81 3/4	2068	24 5/8 x 81 1/4	25 3/4 x 81 3/4	2068	25 1/2 x 81 5/8	26 x 82 1/2
2468	n/a	29 1/4 x 81 3/4	2468	28 5/8 x 81 1/4	29 3/4 x 81 3/4	2468	29 1/2 x 81 5/8	30 x 82 1/2
2668	n/a	31 1/4 x 81 3/4	2668	30 5/8 x 81 1/4	31 3/4 x 81 3/4	2668	31 1/2 x 81 5/8	32 x 82 1/2
2868	n/a	33 1/4 x 81 3/4	2868	32 5/8 x 81 1/4	33 3/4 x 81 3/4	2868	33 1/2 x 81 5/8	34 x 82 1/2
3068	n/a	37 1/4 x 81 3/4	3068	36 5/8 x 81 1/4	37 3/4 x 81 3/4	3068	37 1/2 x 81 5/8	36 x 82 1/2
3668	n/a	43 1/4 x 81 3/4	3668	42 5/8 x 81 1/4	43 3/4 x 81 3/4			
4068	n/a	49 1/4 x 81 3/4	4068	48 5/8 x 81 1/4	49 3/4 x 81 3/4			

*RO WIDTH = DOOR CALL-OUT WIDTH + 1 1/4"

*RO HEIGHT = DOOR CALL-OUT HEIGHT + 1 3/4"

*Assumes standard 3/4" undercut

*RO WIDTH = DOOR CALL-OUT WIDTH + 1 3/4"

*RO HEIGHT = DOOR CALL-OUT HEIGHT + 1 3/4"

*Assumes standard 3/4" undercut

*RO WIDTH = DOOR CALL-OUT WIDTH + 2"

*RO HEIGHT = DOOR CALL-OUT HEIGHT + 2 1/2"

*Assumes standard 3/4" undercut

